SHR-6082

8 Channel 120fps MPEG4 Standalone DVR w/ DVD-RVV



Dimensions (unit:in)

Front/Rear Panel





Summary

The new Samsung SHR-6082 DVR employs MPEG-4 video encoding for 8 channels of camera input and G.723 audio encoding for 4 channels, and supports simultaneous hard drive recording and playback. The SHR-6082 has various back up options such as USB ports and built-in DVD-RW, supports web browser access and records up to 120fps. This DVR also supports network connectivity, providing remote monitoring from a remote PC by transferring video and audio data.

Features

- 8CH DVR
- · Simultaneous Record and Playback of 8-channel video data
- Video (MPEG-4) / Audio(ADPCM)
- Up to 120fps Recording Rate
- 4Ch Audio Inputs and ICh Audio Output
- Combined BNC and VGA Video Output for main display (up to 1280x1024)
- 250 GB SATA HDD Standard
- MAX 5 Internal HDD (HDD x 5)
- Mass storage hard disk backup through high-speed USB 2.0
- Various Search Modes: Time, Event, Backup, POS and Motion Detection
- Built-in DVD-RW
- HDD & DVD SATA Interface
- DDNS Support (Multiple Options)
- Built-in Web Server
- USB Mouse Control
- Event Notifications by E-mail
- · Remote Monitoring function: NET-i Pro and Web viewer

Recommended Accessories

GV-500GBHDS, 500Gb SATA Video Hard Drive GV-1000GBHDS, ITb SATA Video Hard Drive

Specifications

Video	Input	Composite	8 Channel 1.0Vp-p 75Ω
	Output	Composite	2 Channel
		VGA	1 Channel
		Loop Through	8 Channel
	Live	Resolution	D1(704x480)
	Display	Display Speed	240fps
		Display Mode	Single; 4-,6-,8-,9-,13- splits; Sequence; PIP; Freez
Storage	Internal	Default	250 GB SATA
		Expansion Capability	500/1000GB SATA HDD x 5
Audio		Input	4 Channel (RCA Type)
		Output	1 Channel (RCA Type)
Recording		Events	Alarm, Motion, Video Loss, Schedule
		Resolution	CIF (352X240), Half D1 (704x240), D1 (704x480
		Speed	120fps (CIF), 60fps(Half D1), 30fps(D1)
Event		Alarm Function/ Alarm	Record/8 Channel/4 Channel
		Input/ Alarm Output	Tresera, e eriarino, r eriarino.
		Motion Detection	Mode, Sensitivity, Alarm, Duration
		Pre Event Set Time	5.10.20.30 sec
		Post Event Set Time	5,10,20,30 sec / 1,3,5,10,20 min
Playback		Search Mode	Calendar, Event, Time/Date, Text Search(for
		Ocarcii Moac	POS), Motion, Preview
		Display Mode	Single /4-/9-/13-splits
		Play Mode	2x Digital Zoom, Fast Forward/Fast Reverse
		Play Mode	2x, 4x, 8x, 16x, 32x, 64x
Network		Interface	10/100/1000 BaseT
		Protocol	ADSL(PPPoE),DHCP
Control		RS-485	PTZ Control
		Remote Controller	Yes
			1.22
D I		Support Mouse	USB Mouse
Backup		DVD-RW	Yes
		USB	USB 2.0, 3 ports
			USB Memory
			USB External HDD
		Back up Viewer Format	AVI, EXE, DVR
Client S/W		Support OS	Windows XP (Pro), Windows 2000 (Pro),
			Windows Vista (Home Basic/Premium)
		Web Viewer	Support Live/REC/Search
		Remote Viewer	Net-i
Operating Temperature			32°F ~ 104°F (0°C ~ 40°C)
Operating Humidi			20%-85%
Power		Power Supply	Adapter
		Power Source	AC 100-240V
Physical		Dimensions (WxHxD)	17.32 x 3.46 x 16.92 in (440 x 88 x 430mm)
Specifications		Weight	16.35lb (~7.42kg)

